



071 LUBRICATE WITH " MOLY-TEF "
THE COMPONENT :N° **2**

010 FOR NOT SPECIFIED
TIGHTENING TORQUES
SEE NPF 086

| | | | | |
|------|------|---|-----------------|-----|
| 8 | 1 | PIASTRA MOBILE P506-8 M | 48500100000000 | |
| 7 | 2 | DADO AUTOBLOCCANTE M8 ISO 7044 | 15400800008000 | |
| 6 | 2 | SPINA DI GUIDA PIASTRE | 48300210000000 | |
| 5 | 2 | RULLINI PIASTRA P8 COLD DEFF | 48300281000011 | |
| 4 | 2 | VITE M8X30,5 DEFORMATA A FREDDO | 48300133000030 | |
| 3 | 8 | MASCHIO MULTIFASTER 3/8 GAS AISI V1 | 2FFNP38 GAS M2V | 24 |
| 2 | 2 | OR NITRILE 70° SHORE (SPINA P) x NPF075 | OR2,62x9,19 M | |
| 1 | 1 | ETICHETTA FASTER 53x18 | ET002 | |
| POS. | Q.TY | Description | Drawing No. | HEX |

| | | | | |
|--|------------------|---|------------------------|------|
| Faster RIVOLTA D'ADDA-CR-ITALY | | <small>THIS DRAWING IS EXCLUSIVE PROPERTY OF FASTER S.p.A ANY UNAUTHORIZED COPY AND/OR USE ARE STRICTLY PROHIBITED.</small> | | |
| DRAWN | CONFIGURATOR | DESCRIPTION MULTIFASTER MOBILE PART | | |
| DATE | 01/08/2024 | | | |
| SIZE | A2 | GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED): LINEAR DIMENSIONS: ±0.1 ANGULAR DIMENSIONS: ±1° RADIUS AND CHAMFER: ±0.05 SHARP EDGES NOT DIMENSIONED; RADIUS OR CHAMFER MAX. 0.2 | PART NUMBER : | |
| | DIM. MILLIMETERS | CRITICAL | MF-P5068 M=005473=M | |
| | | IMPORTANT | DRAWING N° | |
| | | SECONDARY | DB_MF-P5068 M-005473-M | |
| | | | REVISION | A 10 |